

Scapa 1252

BOPP Packaging Adhesive Tape

DESCRIPTION

Scapa 1252 is a 28 micron bi-axially oriented polypropylene film coated with a rubber based adhesive system, with 45µ total thickness and recommended for general bundling and packaging applications.

APPLICATIONS

- Packing and closing cartons
- Pallet wrapping

PRODUCT BENEFITS

- High tack
- Solvent free.
- Moisture and chemical resistant.
- Applicable by hand or with Scapa HD209 or HD210 dispensers.
- Continuous temperature resistance: +50°C.

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Steel	4.5	N/cm	AFERA 5001
Elongation at Break	170	%	AFERA 5004
Tensile Strength	39	N/cm	AFERA 5004
Total Thickness	0.045	mm	AFERA 5006

Note:

*****This will be taken from the core product for the SAP Material Group*****

STANDARD PRESENTATIONS

- Colours: Buff, Transparent and White
- Core: 76 mm Scapa branded cardboard core
- Packaging: Flat shrink pack
- Roll Length: 66, 100 and 132 metres
- Roll Width: 50 mm

Note:

Other widths may be available upon previous request and will be always subject to minimum order quantities

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C.

Under these conditions, the storage life of the tape in a temperate climate will be at least one year. Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.