

BARNIER® 2721

PVC Lane Marking Adhesive Tape

DESCRIPTION

Scapa 2721 is a 0.16mm premium quality soft PVC tape, which uses an aggressive pressure sensitive rubberbased adhesive system. It combines excellent mechanical strength, easy transversal tearability and abrasion resistance with excellent conformability for use in lane marking and flooring applications

APPLICATIONS

- Ground marking of areas (gyms, workshop, factories)

PRODUCT BENEFITS

- Excellent resistance to abrasion, corrosion and moisture.
- Suitable for indoor and protected outdoor environments.
- conformable
- Easy transversal tearability.
- Environmentally friendly technology.
- Conforms to European Directive 2000/53 EC (lead, chromium VI, mercury, cadmium free).

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Nominal Thickness	0.16	mm	CEI EN 60454
Tensile Strength	25	N/cm	CEI EN 60454
Elongation at Break	150	%	CEI EN 60454
Adhesion to Steel	1.5	N/cm	CEI EN 60454
Adhesion on Backing	1.5	N/cm	CEI EN 60454

Note:

****This will be taken from the core product for the SAP Material Group****

STANDARD PRESENTATIONS

- Colours: Black, Yellow, White, Red, Blue, Light green
- Core: 76mm Scapa branded cardboard core
- Packaging: Heat shrink sleeve
- Roll Length: 33 metres
- Roll Width: 50, 75 and 100mm

RECOMMENDATIONS

Rolls should be stored at on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. The storage temperature should be between +10°C and +25°C.

Use within 24 months of receipt. The tape should be applied with sufficient pressure to ensure an optimum bonding and prevent ageing effects. Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.