

BARNIER® 2724

PVC Hazard Warning Adhesive Tape

DESCRIPTION

Scapa 2724 is a 0.16mm premium quality soft PVC tape, which uses an aggressive pressure sensitive rubberbased adhesive system. It combines excellent mechanical strength, easy transversal tearability and abrasion resistance with excellent conformability. Available in striped colours only.

APPLICATIONS

- special signage, danger zones

PRODUCT BENEFITS

- Excellent resistance to abrasion, corrosion, and moisture.
- Suitable for indoor and protected outdoor environments.
- High abrasion and mechanical resistance.
- Conformable
- Easy transversal tearability.
- Environmentally friendly technology.
- Conforms to European Directive 2000/53 EC (lead, chromium VI, mercury, cadmium free).

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Backing	1.5	N/cm	CEI EN 60454
Adhesion to Steel	1.5	N/cm	CEI EN 60454
Elongation at Break	150	%	CEI EN 60454
Nominal Thickness	0.16	mm	CEI EN 60454
Tensile Strength	25	N/cm	CEI EN 60454

Note:

****This will be taken from the core product for the SAP Material Group****

STANDARD PRESENTATIONS

- Colours: (Striped) Yellow/black, White/red
- Core: 76mm Scapa branded cardboard core
- Packaging: Heat shrink sleeve
- Roll Length: 33 metres
- Roll Width: 50, 75 and 100mm

RECOMMENDATIONS

Rolls should be stored at on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. The storage temperature should be between +10°C and +25°C. Use within 24 months. The tape should be applied with sufficient pressure to ensure optimum bonding and prevent flagging effects.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.